

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
11 December 2003 (11.12.2003)

PCT

(10) International Publication Number
WO 03/101623 A2(51) International Patent Classification⁷: **B05C**

(21) International Application Number: PCT/GB03/02304

(22) International Filing Date: 27 May 2003 (27.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0212614.2 31 May 2002 (31.05.2002) GB

(71) Applicant and

(72) Inventor: **FISHER, Martin** [GB/GB]; 26 Greenlands,
Midway, Swadlincote, Derbyshire DE11 0XS (GB).(74) Agent: **PARNHAM, Kevin**; Swindell & Pearson, 48 Friar
Gate, Derby DE1 1GY (GB).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**Published:**— without international search report and to be republished
upon receipt of that report*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*(54) Title: **APPLICATOR**

(57) Abstract: An applicator is provided in which paint flow is facilitated utilising a grip pump bias to a paint distributor such as roller. The roller is configured within a head such that paint is appropriately distributed with limited leakage in order to allow easy operation for distributing paint upon a surface. The application also includes details of a number of refinements with respect to operation of the applicator at elevated or displaced positions, filling paint containers or canisters and providing greater paint flow control.

WO 03/101623 A2